Equipment and solutions

BE-M Transfer Pump

Product technical datasheet

Transfer pumps for various liquids.



FT-P092 · Rev. 1

Transfer pump designed for pumping fresh water, salt water, wine, milk, vinegar, diesel, oil and olive oil — excluding explosive substances, solid particles or fibres — with a density equivalent to 100 kg/cm³ and kinematic viscosity of 1 mm²/s, and chemically non-aggressive.

Applications

- Transfer of wine, milk, vinegar and water.
- Pumping of diesel, oils and olive oil.
- Transfer of fresh and salt water.

Operating conditions

- Confirm the installation conditions, power supply and duty point before commissioning.

Engineering note	Confirm the installation conditions, power supply and duty point before commissioning.
Complementary equipment	Contact JOVAL for compatible accessories and equipment.
Resources and support	Pump selection guide · JOVAL technical support
Contact	+351 253 490 740 · joval@joval.pt

Technical specifications

Type

Transfer pump

Max Temperature

40 °C

Protection

IP 44

Insulation

Class F

Body

Bronze

Applications

- Transfer of wine, milk, vinegar and water.
- Pumping of diesel, oils and olive oil.
- Transfer of fresh and salt water.

Operating conditions

- Confirm the installation conditions, power supply and duty point before commissioning.

Dimensions and models

Code	Model	kW	HP	V	DN	Max Head	Flow (l/h)
1017000001	BE-M 20	0.37	0.5	230	1/2"	1 - 18	1 700 - 300
1017000002	BE-M 25	0.4	0.6	230	3/4"	1 - 14	2 400 - 300
1017000003	BE-M 30	0.74	0.9	230	1"	1 - 14	4 800 - 300
1017000004	BE-M 40	0.75	1	230	1" 1/4	1 - 17	5 400 - 300

Engineering note Confirm the installation conditions, power supply and duty point before commissioning.