



# Franklin Electric

## 4" REWINDABLE MOTORS



### Specifications:

- Outer casing, shaft and bolts: Stainless steel AISI 304
- Coupling flange: Cast iron with anti-corrosive treatment
- Stator: Rewindable
- Max. working temperature: 35°C
- Cooling fluid: non toxic
- Max. starts/hour: 30
- Min. cooling flow: 8 cm/s
- Degree of protection: IP 68
- Max. depth: 350 m
- Mounting: vertical or horizontal

Code	Model	kW	HP	V	A	Capacitor uF	Axial Load N	Weight kg
2034110037	<b>NS4MG MH 2037</b>	0,37	<b>0,5</b>	230	3,1	20	2500	9,5
2034110055	<b>NS4MG MH 2055</b>	0,55	<b>0,75</b>	230	4,3	25	2500	10,5
2034110075	<b>NS4MG MH 2075</b>	0,75	<b>1</b>	230	5,3	35	2500	11,8
2034210110	<b>NS4MG MH 2110</b>	1,1	<b>1,5</b>	230	7,8	40	2500	13,5
2034210150	<b>NS4MG MH 2150</b>	1,5	<b>2</b>	230	10,1	50	2500	16,5
2034510220	<b>NS4MG MH 2220</b>	2,2	<b>3</b>	230	13,5	80	2500	19,5

2034130037	<b>NS4MG TH 2037</b>	0,37	<b>0,5</b>	400	1,2		2500	8
2034130055	<b>NS4MG TH 2055</b>	0,55	<b>0,75</b>	400	1,6		2500	8,9
2034130075	<b>NS4MG TH 2075</b>	0,75	<b>1</b>	400	2,5		2500	10,2
2034230110	<b>NS4MG TH 2110</b>	1,1	<b>1,5</b>	400	2,8		2500	11,5
2034230150	<b>NS4MG TH 2150</b>	1,5	<b>2</b>	400	3,8		2500	13,5
2034530220	<b>NS4MG TH 2220</b>	2,2	<b>3</b>	400	6,2		2500	16,5
2034530300	<b>NS4MG TK 2300</b>	3	<b>4</b>	400	7,2		4500	18,5
2034530400	<b>NS4MG TK 2400</b>	4	<b>5,5</b>	400	9,7		4500	22,5
2034530550	<b>NS4MG TK 2550</b>	5,5	<b>7,5</b>	400	13,5		4500	27,5
2034530750	<b>NS4MG TK 2750</b>	7,5	<b>10</b>	400	17,8		4500	28,5

**Cable included**

**Capacitor not included**

Code	Model	kW	HP	V	A	Capacitor uF	Axial Load N	Weight kg
------	-------	----	----	---	---	-----------------	-----------------	--------------

2034511037	NS4MX MH 2037	0,37	0,5	230	3,1	20	2500	9,5
2034511055	NS4MX MH 2055	0,55	0,75	230	4,3	25	2500	10,5
2034511075	NS4MX MH 2075	0,75	1	230	5,3	35	2500	11,8
2034512110	NS4MX MH 2110	1,1	1,5	230	7,8	40	2500	13,5
2034512150	NS4MX MH 2150	1,5	2	230	10,1	50	2500	16,5
2034515220	NS4MX MH 2220	2,2	3	230	13,5	80	2500	19,5

2034531037	NS4MX TH 2037	0,37	0,5	400	1,2		2500	8
2034531055	NS4MX TH 2055	0,55	0,75	400	1,6		2500	8,9
2034531075	NS4MX TH 2075	0,75	1	400	2,5		2500	10,2
2034532110	NS4MX TH 2110	1,1	1,5	400	2,8		2500	11,5
2034532150	NS4MX TH 2150	1,5	2	400	3,8		2500	13,5
2034535220	NS4MX TH 2220	2,2	3	400	6,2		2500	16,5

2034535300	NS4MX TK 2300	3	4	400	7,2		4500	18,5
2034535400	NS4MX TK 2400	4	5,5	400	9,7		4500	22,5
2034535550	NS4MX TK 2550	5,5	7,5	400	13,5		4500	27,5
2034535750	NS4MX TK 2750	7,5	10	400	17,8		4500	28,5

**Cable included**

**Capacitor not included**